

TECHNICAL DATA SHEET

IMAGES IN RELIEF



REFERENCE

IER-3D

DESCRIPTION

Reproduction of images and designs in three dimensions on colourful wood



FEATURES

- Materials
- ◆ Natural MDF (brown)
 - ◆ Damp-proof mass tinted MDF (blue,red,yellow,orange,green,grey,black,brown)
 - ◆ Acrylic resin
 - ◆ Multilayer MDF (formed by several layers of mass tinted MDF)

Max. thickness (mm) ◆ 10 to 50

Max. Depth (mm) ◆ 4 to 45 according to panel thickness

Fireproofing according to EN 13501-1 ◆ D - s2, d0 (MDF)
For other grades and materials, contact with DECUSTIK

Density (kg/m²) ◆ Depending on the percentage of machining

Sizes ◆ Standard dimension 2400x1200mm (MDF)

⁽¹⁾ ◆ Max. dimension 3000x1500mm (MDF)
For other dimensions and materials, contact with DECUSTIK

Finishing

- ◆ Ecru
- ◆ White lacquered / color ⁽²⁾⁽³⁾-according to RAL colour chart
- ◆ Varnished ⁽²⁾⁽³⁾
- ◆ Metallic lacquered ⁽²⁾⁽³⁾-according to RAL colour chart

Edge machining

- ◆ Viewed
- ◆ Grooving
- ◆ Dovetailing



APPLICATIONS

- ◆ Wall covering
- ◆ Ceiling
- ◆ Furniture accessories

ACCESSORIES FOR ASSEMBLY

Edge profiles ◆ Edge profiles, corners and ends (wall covering)
◆ 45° angle

Fixing system ◆ Wall covering: standard system according to edge machining

- viewed
- grooving
- dovetailing

NOTES

(1) Dimensions per panel. A wall paneling is made by multiple panels.

(2) Available in normal and fire-proof quality

(3) Matt, satin or glossy finishing